

CARACTERISTIQUES MATERIELLES

Interface	USB 3.0
Dimensions (LxPxH)	40.5 × 19.72 × 10.29mm
Type d'antenne	Omni Directional

CARACTÉRISTIQUES WIFI

Standards WiFi	IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Fréquence WiFi	5GHz 2.4GHz
Débits Maximaux	5GHz 11ac: Up to 867Mbps(dynamic) 11n: Up to 300Mbps(dynamic) 11a: Up to 54Mbps(dynamic) 2.4GHz 11n: Up to 400Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
Sensibilité de réception	5GHz: 11a 6Mbps: -91dBm 11a 54Mbps: -76dBm 11n HT20: -71dBm 11n HT40: -70dBm 11ac HT20: -68dBm 11ac HT40: -64dBm 11ac HT80: -62dBm 2.4GHz: 11b 11Mbps: -86dBm 11g 54Mbps: -73dBm 11n HT20: -71dBm 11n HT40: -70dBm
Puissance de transmission	<23dBm (EIRP)
Modes WiFi	Ad-Hoc / Infrastructure Mode
Sécurité WiFi	Support 64/128 bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Technologie de modulation	DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM

AUTRES

Certification	CE, FCC, RoHS
Contenu de l'emballage	AC1300 Mini Wireless MU-MIMO USB Adapter Archer T3U Quick Installation Guide Resource CD
Système requis	Windows 11/10/8.1/8/7/XP, Mac OS 10.15 and earlier
Environnement	Operating Temperature: 0°C~40°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing